



Balancing a Community's Wastewater Aspirations with Affordability – The Gisborne Experience

Rachael Shaw, CH2M Beca Ltd

Introduction

- Background and Context
 - Consents
 - Enhanced Wetland Pond System Trial (EWPS)
 - Scaling up
 - Value Engineering
 - Conclusions
-
- Acknowledgements: Gisborne District Council, Wastewater Technical Advisory Group, NIWA, ESR, Northcott Research Ltd





Wastewater History


- 1964 – untreated wastewater to Marine outfall
- 1990 – 2010 milliscreen plant
- 2010 – BTF Stage 1
- 2015 - 2017 Stage 2 AUD investigations, long term treatment & disposal
- 2016 –EWPS pilot and concept design

“The permit holder shall use its best endeavors to adopt those AUD options that are identified as feasible and which will enable the progressive removal of the treated human sewage from the discharge, via the marine outfall, with the objective of complete removal by 2020.”

(Watson, June 2009)



Existing Banks St Treatment Plant



WTAG and the EWPS Pilot

- WTAG Key Objective → use natural treatment to restore the *mauri* or life force of the wastewater
- undertook series of investigations culminating in selection of Enhanced wetland pond system (EWPS) pilot
- Pilot Objective
 - *Is alternative treatment of Gisborne's domestic WW feasible?*
 - *What level of treatment can be achieved through a tertiary enhanced wetland & pond system?*
 - *Identify potential performance issues*
 - *Confirm basis for scale up*
 - *Operated between January & June 2016*
 - *NIWA, ESR and GDC collaboration*



BTF
effluent
from
outflow
weir



Sludge settler for biosolids (sludge) removal from BTF effluent



High Rate Algal Ponds (HRAPs) for sunlight disinfection, organic compound (e.g. BOD₅) and nutrient removal



Algal Harvester (AH) for algal solids removal from the HRAP effluent



Surface Flow Constructed Wetland (SFCW) for further organic compounds and nutrient removal



Woodchip Denitrification Filter for residual nitrate removal via disinfection



Final Surface Flow Constructed Wetland (HW) for further polishing the BTF effluent before discharge

Discharge to habitat wetland or alternative use

Pilot Performance


Table 1: Mean Pilot Plant Final Effluent Quality and Removal Efficiency Across EWPS (Tanner, 2016)

Parameter	TSS (mg/L)	cBOD5 (mg/L)	NH4-N (mg/L)	TN (mg/L)	TP (mg/L)	E.coli (cfu/100ml)
Raw influent to WWTP#	199	206	NM	NM	NM	NM
Post BTF (unsettled) #	71	27	NM	NM	NM	NM
Influent to HRAP Concentration (post settlement)	6.4	8.0	5.69	10.14	3.36	3.8E+0.4
Effluent Concentration	4.3	2.9	0.32	2.1	1.4	1.5E+1
Removal efficiency across EWPS	33%	64%	94%	80%	59%	3 log reduction
Removal efficiency across complete treatment system	97.7%	98.7%	NM	NM	NM	NM

NM Not Measured

Based on compliance monitoring data for period 23 February to 7 June 2017

EWPS Process Flow



Scale up - Location





Figure 1: EWPS Hypothetical Site Study Area

EWPS Scale-Up Design Factors

- Unknown site → distance, size, topography, neighbours
- Geotech factors → Soil type, stability, seismic risk
- Depth to groundwater → have to build up
- Lining requirements
- Prototype design for sludge and algal settlement with 1:1 bund batters
- Scalability of system
 - Access and maintenance
 - Treatment performance,
 - Nuisance affects
 - Constructability



Figure 2-3: High Rate Algal Ponds in California (a & b), New Mexico (c, d & e) and New Zealand (f & g).

Option 1 - Alternative Treatment Layout


82ha of process plant area,
not including buffers

Gross area required 100 -
160ha depending on buffers


Capital Cost:

\$67.4M - \$74.9M
(4 - 8km pipeline)


REFERENCE SIZES:



PROCESS AREAS:



Algal settlers &
digesters



Sludge settlers &
digesters

HRAPS


HRAPS

Wetland 2

Wetland 1


Woodchip
Filters

Option 2 – Solids Removal at Banks St



Conventional Treatment at Banks St

- Clarifier + Solids Handling ~\$17.7M
- 2nd BTF ~ \$10M
- UV ~ \$0.8M
- Total Capital Cost: \$28.5 M



Value Engineering


- Work-shopped with WTAG October
- Significant cost reduction required significant changes to the original natural treatment concept
- Some objectives may not be fully met
- Treatment processes priced as “building blocks”
- Where do you get the most benefit/cost
- What are the cost reduction opportunities?
 - Reduce, downsize, eliminate
 - Conventional + Natural Hybrid schemes



Value Engineering Options

Option	General Overview	Type of Treatment	WOL ranges (\$M)
Option A	(Option 2) Conventional solids removal, thickening and dewatering processes.	Conventional	\$35
Option B	Second BTF for biotransformation and provide redundancy	Conventional	\$12M
Option C & D	Second BTF + solids removal + disinfection, improving the “transformational”/cultural objectives of the Scheme, and limiting the process risk through the use of conventional treatment processes.	Conventional	\$48 - 61
Options E, F & G:	<p>Conventional solids removal and disinfection with elements of the EWPS to provide BOD and nutrient removal, with or without a second BTF.</p> <p>This allows for more fulfilment of the cultural objectives of the system through the use of additional natural treatment processes</p>	Hybrid	\$77 – \$94
Options H, I, J & K:	<p>Provide all further wastewater treatment at a remote site using either the full EWPS system (as described in Option 1) or significant elements of it combined with conventional UV disinfection.</p> <p>This provides the most fulfilment of the cultural objectives of the system.</p>	Natural	\$56 - 89

WOL Cost Comparison of Options



Conclusion

- EWPS can achieve high level of effluent polishing but may be more suited to smaller communities.
- Multiple units in series and parallel increase complexity of distribution. For natural processes to be cost effective, require simple configurations
- Conveyance to and from remote sites can form a disproportionate part of the overall scheme cost
- Options need to be aligned to the possible receiving environments and Community objectives to maximise the benefit for the cost (capital and whole of life)
- Identify end use markets for both effluent and solids and design treatment to suit.